

| RLC-823A-IP-Camera-Specifications | | |
|-----------------------------------|--|---|
| | Model | RLC-823A |
| Video & Audio | Image Sensor | 1/2.8" CMOS sensor |
| | Video Resolution | Default: 3840X2160 (8.0 Megapixels) at 25 frames/sec |
| | Lens | f=2.7-13.5mm F=1.6-3.3, zoom module |
| | Optical Zoom | 5X |
| | Video Format | H.265 |
| | Field of View | Horizontal: 96°-27° |
| | | Vertical: 69°-21° |
| | Day & Night | Auto-switching with IR-cut filter |
| | Infrared Night Vision | Up to 60 meters (190 ft) (LED: 4pcs/28mil/850nm) |
| Color Night Vision | Spotlight: 3pcs/5700K/945 lumens | |
| Power | Audio | Two-way audio |
| | PoE | IEEE 802.3at, 48V Active |
| Interface | DC Power | DC 12.0V-2A, <24W |
| | Power | DC power port |
| | System | Reset button |
| | Ethernet | One 10M/100Mbps; RJ45 |
| | Storage | Micro SD card slot (Max. 256GB) |
| Pan & Tilt | Audio | Built-in microphone and speaker |
| | Pan & Tilt Range | Pan: 360°, Tilt: 0° ~ 90° |
| | Pan Speed | 2.5°-150°/s (Speed can be set) |
| | Tilt Speed | 1.5°-60°/s (Speed can be set) |
| | Preset | 64 |
| | Patrol | 1 Patrol; up to 16 presets per patrol |
| | Auto Tracking | Support |
| Software Features | Power-off Memory Function | Support |
| | Frame Rate | Mainstream: 2fps - 25fps (default: 25fps) |
| | | Substream: 4fps - 15fps (default: 10fps) |
| | Code Rate | Mainstream: 4096Kbps - 8192Kbps (default: 6144Kbps) |
| | | Substream: 64Kbps - 512Kbps (default: 256Kbps) |
| | Browsers Supported | Edge, Chrome, Firefox, Safari |
| | OS Supported | PC: Windows, Mac OS; Smartphone: iOS, Android |
| | Smart Alarm | Motion detection; person detection; vehicle detection; pet detection (beta) |
| | Record Mode | Motion-triggered recording (default); 24/7 recording; scheduled recording |
| Protocols & Standards | HTTPS, SSL, TCP/IP, UDP, HTTP, IPv4, UPnP, RTSP, RTMP, SMTP, NTP, DHCP, DNS, DDNS, FTP, P2P | |
| Maximal User Access | 20 Users (1 admin account & 19 user accounts); support up to 12 simultaneous video streams (10 substreams & 2 mainstreams) | |
| Working Environment | Smart Home | Google Assistant |
| | Temperature | Operating temperature: -10°C ~ +55°C (14°F ~ 131°F) |
| | Humidity | Operating humidity: 10% ~ 90% |
| Size & Weight | Waterproof | IP66 |
| | Dimension | Φ136*201mm |
| Warranty | Weight | 1.8kg |
| | Limited Warranty | 2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/ |

Δήλωση συμμόρφωσης ΕΕ (GR)

Manufacturer: REOLINK INNOVATION LIMITED

Address: FLAT/RM 705 7/F FA YUEN COMMERCIAL BUILDING 75-77 FA YUEN
STREET MONG KOK KL HONG KONG

Αυτή η δήλωση συμμόρφωσης εκδίδεται με αποκλειστική ευθύνη του κατασκευαστή και ανήκει στο ακόλουθο προϊόν:

Τύπος Προϊόντος: IP Κάμερα

Μοντέλο: RLC-811A, RLC-1220A, RLC-1210A, RLC-823A, RLC-822A

Το αντικείμενο της δήλωσης που περιγράφεται παραπάνω είναι σύμφωνο με τη σχετική Νομοθεσία εναρμόνισης της Ένωσης:

- EMC Directive: 2014/30/EU
- RoHS Directive: 2011/65/EU

Έχουν εφαρμοστεί τα ακόλουθα εναρμονισμένα πρότυπα και τεχνικές προδιαγραφές:

| | |
|------|--|
| EMC | EN 55032:2015/A11:2020 EN 61000-3-2:2019 EN 61000-3-3:2013/A1:2019 EN 55035:2017/A11:2020 |
| RoHS | EN 50581:2012 |

Υπογράφηκε για και για λογαριασμό του: REOLINK INNOVATION LIMITED

Τόπος έκδοσης: Hong Kong

Ημερομηνία έκδοσης: 15-9-2021

Όνομα: Wang aijun

Θέση: Τεχνικός διευθυντής

Υπογραφή:

Wang aijun

EU Declaration of Conformity (EN)

Manufacturer: REOLINK INNOVATION LIMITED
Address: FLAT/RM 705 7/F FA YUEN COMMERCIAL BUILDING 75-77 FA YUEN
STREET MONG KOK KL HONG KONG

This declaration of conformity is issued under the sole responsibility of the manufacturer and belongs to the following product:

Product Type: IP Camera

Model: RLC-811A, RLC-1220A, RLC-1210A, RLC-823A, RLC-822A

The object of the declaration described above is in conformity with the relevant Union harmonization legislation:

- EMC Directive: 2014/30/EU
- RoHS Directive: 2011/65/EU

The following harmonized standards and technical specifications have been applied:

| | |
|------|--|
| EMC | EN 55032:2015/A11:2020 EN 61000-3-2:2019 EN 61000-3-3:2013/A1:2019 EN 55035:2017/A11:2020 |
| RoHS | EN 50581:2012 |

Signed for and on behalf of: REOLINK INNOVATION LIMITED

Place of issue: Hong Kong
Date of issue: 15-9-2021
Name: Wang aijun
Position: Technical Director
Signature:

Wang aijun